



J&A (International) Limited

THE GARMENT DECORATION SPECIALISTS

TECHNICAL DATASHEET

FR Security Pockets



www.ja-int.com | +44 (0)1790 752 757

J&A (International) Ltd. Insignia House, Vale Road, Spilsby, Lincolnshire PE23 5HE

FR Security Pockets



TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C): 210°C
Temperature (°F): 410°F
Time: 15 - 20 seconds
Pressure: High 56.9 - 71.1 psi / 3.9 - 4.9 bar / 4.0 - 5.0 kg/cm²
Special Note: Pre-press recommended

LAUNDERING

Suitable for Industrial Laundering up to 85°C
Suitable for Industrial Drying Techniques - Medium
Suitable for Dry-Cleaning
Iron - Medium, On Reverse
Do Not Bleach
Do Not wash with strong Acid or Alkaline additives

HANDLING AND STORAGE

Store in a cool, dry environment at a stable temperature of ~20°C
Store away from direct sunlight

COMPOSITION

Layered Flame Retardant, Polycotton Fabric construction
Ink - Solvent-based (Optional)
100% Polyester Flame Retardant Thread
Thermoplastic Polyester Adhesive Film

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user
No PPE is required during application**

ENVIRONMENTAL / RECYCLING

Non-Recyclable

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.