Visibility Transfers

TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C):	150-180°C	
Temperature (°F):	302-356°F	
Time:	10 seconds	
Pressure:	Medium	42.7 - 56.9 psi / 2.9 - 3.9 bar / 3.0 - 4.0 kg/cm2
Carrier Release:	Cold peel	

LAUNDERING
Suitable for domestic wash up to 40°C
Tumble Dry - Medium
Iron - Medium, On Reverse
Do Not Dry-Clean
Do Not Bleach

HANDLING AND STORAGE
Store in a damp-free environment at a stable temperature of ~20°C
Keep away from direct sunlight
No personal protection equipment is required in handling and storage
Do not attempt to apply any transfer that has been removed from its carrier

COMPOSITION
Ink - Solvent based with glass bead coating
Adhesive - Polyester
Carrier - Polyester sheeting with glass-bead coating

HEALTH & SAFETY
This product is identified as Non-Hazardous to the end user
No PPE is required during application**

ENVIRONMENTAL / RECYCLING
Non-Recylable
Vegan-Friendly: No

CERTIFICATION
Flame Retardant: EN ISO 11611 & EN ISO 11612

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.